

METHOD OF MANUFACTURING COMPOSITE MOLDED PRODUCT,  
INCLUDING COATING FOR INSERT MATERIAL  
WITH DOPE CEMENT BEFORE INSERT MOLDING

5

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a method of manufacturing a composite molded product, so as to improve the adhesion between a synthetic resin and an insert material  
10 such as metal, resin, inorganic material, or the like, in the insert molding.

Description of the Related Art

Conventionally, composite molded products, each consisting of (i) a smooth wood panel having a top wood layer and (ii) a synthetic-resin core material, are used as  
15 materials for quality furniture or the interior of deluxe cars.

Additionally, in fields such as that of sound-damping and sound-insulating materials, composite steel plates, and various kinds of shielding materials, and in particular, in the fields such as those involving the adhesion between steel plates and the adhesion and composition of a steel plate and a plastic material, use of a plastic outside  
20 plate has been examined so as to improve the weatherability and to reduce the weight and the cost.

In order to obtain such composite molded products, insert molding is typically performed in which (i) an insert material as a top layer, which is made of metal, synthetic resin, inorganic material, or the like, is prepared, (ii) the back face of the insert  
25 material is coated with primer, and (iii) this insert material is installed in a mold of the

injection molding so as to inject synthetic resin and mold a synthetic resin base at the back-face side of the insert material.

However, in this method, the time during which the primer is maintained to be active is short. Therefore, the injection molding should be executed in a very short time after the coating using the primer is performed. Additionally, such coating using the primer must be performed immediately before the insert molding. Therefore, it is difficult to uniformly coat an insert material with primer if the shape of a product to be manufactured is complicated. Also in this method, adhesion between the insert material and the base resin is inferior; thus, molded products may have a portion which breaks away or protrudes.

#### SUMMARY OF THE INVENTION

In consideration of the above circumstances, an object of the present invention is to provide a method of manufacturing a composite molded product, so as to improve the adhesion between the insert material and the base resin.

Therefore, the present invention provides a method of manufacturing a composite molded product, comprising the steps of:

coating an insert material with dope cement; and  
subjecting the insert material coated with the dope cement to insert molding.

The present invention also provides a method of manufacturing a composite molded product, comprising the steps of:

coating an insert material with primer;  
coating surface of the primer with dope cement; and  
subjecting the insert material coated with the dope cement to insert molding.

In the above methods, typically, the dope cement is obtained by dissolving a

synthetic resin in a solvent, where the synthetic resin is injected synthetic resin in the insert molding or synthetic resin which has compatibility with the injected synthetic resin.

According to the present invention, adhesion between the insert material and the base resin is superior; thus, substandard products having a portion which breaks away or protrudes are hardly generated. In addition, a surface material in which the insert material is coated with the dope cement has a very small degree of camber; thus, punching or the like for shaping the surface material can be easily performed after the coating.

Furthermore, according to the dope cement, sufficient time can be obtained before the start of injection molding. Therefore, even if the shape of a product to be manufactured is complicated, the plate before forming the shape can be uniformly coated with the dope cement. In addition, the plate after the coating has a very small degree of camber; thus, punching or the like for shaping the plate can be easily performed.

The present invention also provides a method of manufacturing a composite product, comprising the steps of:

applying a solution, which comprises a first synthetic resin and a solvent, over a substrate to form a first layer comprising said first synthetic resin; and

forming a second layer, which comprises a second synthetic resin compatible with said first synthetic resin, on said first layer.

This method may further comprise the step of removing said solvent to form said first layer over said substrate, or the step of coating the surface of said substrate with primer.

In the above method, said second layer may be formed on said first layer by

injection molding. Typically, said substrate is made of as least one material selected from metal, resin, and inorganic material.

#### BRIEF DESCRIPTION OF THE DRAWINGS

5 Fig. 1 is a general cross-sectional view showing the structure of an example of the composite molded product manufactured by using the manufacturing method according to the present invention.

Fig. 2 is a general cross-sectional view showing an example of the arrangement in which the surface material is installed in the cavity of a mold used in the injection  
10 molding, according to the present invention.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereinafter, embodiments according to the present invention will be explained in detail.

15 Fig. 1 is a general cross-sectional view showing the structure of an example of the composite molded product manufactured by using the manufacturing method according to the present invention.

In the figure, reference numeral 1 indicates an insert material. This insert material 1 is formed in advance to have a shape corresponding to the mold used in the  
20 insert molding, that is, a shape approximately corresponding to a final composite product. One of the surfaces of the insert material 1 is treated to form a surface-treated layer 2. This surface-treated layer 2 is coated with primer to have a primer film 3. The primer film 3 is then coated with dope cement to have a dope cement film 4, so that a surface material 5 is obtained.

25 In the present invention, the surface-treated layer 2 and the primer film 3 may

be omitted.

As shown in Fig. 2, the surface material 5 is installed in the cavity of a mold 7 used in the injection molding in a manner such that the dope cement film 4 faces the cavity (i.e., the insert material 1 faces the wall of the mold 7). The shape of the cavity in the mold 7 corresponds to the shape of a final molded product. Then the injection molding is executed so as to inject synthetic resin towards the dope cement film 4 of the surface material 5, thereby combining the synthetic resin and the surface material 5. This composite is then taken out from the molds 7 and 8 of the injection molding, so that a composite molded product 10 consisting of the surface material 5 and a base resin layer 6 is obtained.

The insert material 1 in the present embodiment is metal, resin, inorganic material, or the like.

Typically, aluminum, aluminum alloy, stainless steel, carbon steel, or copper may be used as the metal.

As the resin, polycarbonate, polyester/polycarbonate, polyethylene, polypropylene, polyethylene terephthalate, poly(methyl methacrylate), or the like, may be used.

As the inorganic material, alumina, glass, ceramics, concrete, natural stone, or the like, may be used.

At least one of the surfaces of the insert material 1 is treated so as to improve the adhesion, thereby forming the surface-treated layer 2. When the insert material 1 is metal, the surface treatment (method) called Alumite, Alodine (Alocrom), etching, or the like, may be employed. When the insert material 1 is resin or inorganic material, sanding, shot blasting, or the like, may be employed as the surface treatment.

Here, even if the surface treatment is omitted in the present invention, the dope

cement film 4 provides sufficient strength of adhesion between the insert material 1 and the base resin layer 6.

The primer in the present embodiment may be epoxy, urethane, rubber, acrylic, polypropylene, or vinyl paint (or coating). Such paint is generally used in adhesion, painting, coating, laminating, or composition applied to aluminum, aluminum alloy, stainless steel, carbon steel, copper, polycarbonate, polyester/polycarbonate, polyethylene, polypropylene, polyethylene terephthalate, poly(methyl methacrylate), alumina, glass, ceramics, concrete, or the like.

A concrete example of the epoxy primer is two-liquid epoxy primer having major components of (i) multifunctional epoxy resin such as cyclic fatty acid epoxy resin, glycerin-type epoxy resin, dimer acid modified epoxy resin, or a reactant between bisphenol A and epichlorohydrin, and (ii) polyamine such as polyaminoamide compound, aliphatic polyamine, cyclic aliphatic polyamine, or aromatic polyamine.

The following are concrete examples of the urethane primer: two-liquid urethane primer having major components of (i) multifunctional polyisocyanate which is a multifunctional polyisocyanate compound having an isocyanate group at the end, and (ii) polyol such as polyether polyol or polycarbonate polyol, and single-liquid urethane primer having a major component of multifunctional polyisocyanate.

The following are concrete examples of the rubber primer: natural rubber, styrene-butadiene rubber, polybutadiene rubber, polyisobutylene, polychloroprene, polyacrylate rubber, and polyvinyl ether rubber.

The following are concrete examples of the acrylic primer: multifunctional methacrylic acid ester and multifunctional acrylic acid ester.

The following are concrete examples of the polypropylene primer: polypropylene and chlorinated polypropylene.

The following are concrete examples of the vinyl primer: polyvinyl butyral, polyvinyl formal, polyvinyl acetacetal, and vinyl ether such as divinyl ether or dibutylvinyl ether.

5 The insert material 1 or the surface-treated layer 2 is coated with one or more layers of such primer. The method such as printing, spraying, rolling, or flow coating can be employed for the coating with the primer.

The surface coated with the primer is dried at a temperature from room temperature to 50°C, thereby forming the primer film 3. The thickness of the primer film 3 is 1 to 100  $\mu$  m, preferably, 5 to 20  $\mu$  m.

10 The dope cement used in the present embodiment is a solution obtained by dissolving a synthetic resin in a solvent, where this synthetic resin is one used for the base resin layer 6 or one having compatibility with the base resin layer 6. Such dope cement has very superior adhesion with respect to the insert material 1 as an adherend.

The following are concrete examples of the above synthetic resin: (i) styrene resin such as acrylonitrile-butadiene-styrene copolymer (abbreviated as "ABS" hereinbelow), acrylonitrile-styrene copolymer (abbreviated as "AS" hereinbelow), or polystyrene, (ii) vinyl polymer resin such as polyvinyl chloride or polyvinylidene chloride, (iii) acrylic resin such as polymethyl methacrylate, (iv) polycarbonate resin, (v) polyamide resin, (vi) polyolefin resin such as polyethylene or polypropylene, and (vii) 15 polyester resin such as polyethylene terephthalate or polybutylene terephthalate. These kinds of resin are used alone or in a mixture in which two or more kinds of resin are mixed. If difficult-to-dissolve synthetic resin such as polyethylene is used, powder of this synthetic resin is suspended or mixed with easily-soluble synthetic resin such as 20 ABS resin.

The solvent may be acetone, methanol, isopropanol, toluene, xylene, methyl acetate, isobutyl acetate, butyl acetate, methyl ethyl ketone, or methyl isobutyl ketone. These kinds of solvents are used in a single kind or a mixture, according to the kind of the synthetic resin which is dissolved in the solvent.

5           The insert material 1 may be directly coated with such dope cement, or the surface-treated layer 2 may be coated with the dope cement, or the primer film 3 may be coated with the dope cement. The coated portion is then dried in an atmosphere at a temperature from room temperature to 50°C, thereby forming the dope cement film 4. Similar to the primer, the method such as printing, spraying, rolling, or flow coating can  
10 be employed for the coating with the dope cement.

The thickness of the dope cement film 4 is 5  $\mu\text{m}$  or more, preferably, 25 to 70  $\mu\text{m}$ .

The following are concrete examples of the synthetic resin of which the base resin layer 6 is made: (i) styrene resin such as acrylonitrile-butadiene-styrene  
15 copolymer (abbreviated as "ABS" hereinbelow), acrylonitrile-styrene copolymer (abbreviated as "AS" hereinbelow), or polystyrene, (ii) vinyl polymer resin such as polyvinyl chloride or polyvinylidene chloride, (iii) acrylic resin such as polymethyl methacrylate, (iv) polycarbonate resin, (v) polyamide resin, (vi) polyolefin resin such as polyethylene or polypropylene, and (vii) polyester resin such as polyethylene  
20 terephthalate or polybutylene terephthalate. These kinds of resin are used alone or in a mixture in which two or more kinds of resin are mixed.

As the dope cement film 4 has compatibility with the base resin layer 6, the degree of adhesion between the dope cement and the base resin is superior regardless of the elapsed time, that is, even after a few hours or days passed. In addition, after the



insert material 1 having a plate shape is coated with dope cement and is then dried, the plate can be subjected to blanking or press working so as to form a desired shape.

Therefore, even if the shape of the surface material 5 is complicated, the plate before forming the shape can be uniformly coated with the dope cement.

- 5           The various combinations between the insert material, surface treatment, primer, dope cement, solvent, and base resin are possible as shown in Table 1.

Table 1

insert material		surface treatment	primer	dope cement		base resin
				resin	solvent	
metal plate	aluminum	Alumite Alodine etching	epoxy urethane rubber poly- propylene vinyl	ABS AS polystyrene poly(vinyl chloride) acrylic poly- carbonate polyamide	acetone	ABS AS polystyrene poly(vinyl chloride) acrylic poly- carbonate polyamide
	stainless steel	etching			methanol	
	copper	etching			isopropanol	
resin	PPS	sanding shot blasting	epoxy urethane acrylic poly- propylene vinyl		toluene	
	FRP	sanding shot blasting			xylene	
inorganic material	alumina	sanding shot blasting	epoxy rubber poly- propylene vinyl		methyl acetate	
	glass	sanding shot blasting			isobutyl acetate	
	stone	sanding shot blasting			butyl acetate	
				methyl ethyl ketone		
				methyl isobutyl ketone		

- 10           The composite molded product 10 formed by the process as explained above has sufficient adhesion between the insert material 1 and the base resin layer 6; thus, substandard products having a portion which breaks away or protrudes are hardly generated. In addition, the surface material 5 in which the insert material 1 is coated with the dope cement 4 has a very small degree of camber; thus, punching or the like for
- 15   shaping the surface material 5 can be easily performed after the coating.

Below, practical examples will be explained.

First, the dope cement was made under the following conditions: 40 g of ABS resin (product name: Stylac-ABS, manufactured by Asahi Kasei Corporation) pellets was dissolved in 100 g of acetone. This solution was diluted with the same amount of toluene, thereby making the dope cement.

In the next step, after a surface-treated face of an aluminum thin plate having a thickness of 0.5 mm was coated with primer, the coated face was further coated with the above dope cement. The coated face was then dried, so that a dope cement film was formed.

Similar processes were repeated for different kinds of primer, and for different thicknesses ( $\mu\text{m}$ ) of the dope cement. After the coating with the dope cement, each aluminum thin plate was left to stand for one or more days or months at ordinary temperature. The aluminum thin plate was then installed in the cavity of a mold used in the injection molding, and ABS resin (product name: Stylac-ABS, manufactured by Asahi Kasei Corporation) for forming the base resin layer was injected into the mold, so that a composite molded product was obtained.

The strength of adhesion between the aluminum thin plate and the base resin layer of each composite molded product was measured. The results of measurement are shown in Table 2.

Table 2

primer	dope cement	thickness of dope cement film (μm)	elapsed time after coating	adhesion strength (MPa)
vinyl + urethane (double layer)	ABS	70	one day	13.5 or more (rupture at ABS layer)
			one month	
			three months	
	no dope cement	—	0 days	3.9
			one day	0.9
	ABS	25	8.7	
		15	4.4	
		10	3.5	
		5	2.9	
		70	13.5 or more (rupture at ABS layer)	
		45		
		25		
		70	13.5 or more (rupture at ABS layer)	
		45		
		25		
polypropylene + urethane (double layer)		70	11.0	
polypropylene (single layer)		70	no adhesion	
		no primer		

With reference to Table 2, each composite molded product using the primer and the dope cement, in which the thickness of the dope cement is 25 to 70  $\mu\text{m}$ , maintains sufficient adhesion even when one or more days or months have passed after the coating with the dope cement.

The insert material 1 may be made of wood. In this case, (i) the surface treatment called sanding may be used, or no surface treatment may be performed, (ii) the primer is not always necessary (i.e., may be used), (iii) dope cement as explained above may be used, and (iv) synthetic resin as explained above may be used for a base resin layer.

Although the invention has been described in detail herein with reference to its preferred embodiments and certain described alternatives, it is to be understood that this

description is by way of example only, and it is not to be construed in a limiting sense.

It is further understood that numerous changes in the details of the embodiments of the invention, and additional embodiments of the invention, will be apparent to, and may be made by, persons of ordinary skill in the art having reference to this description. It is

5 contemplated that all such changes and additional embodiments are within the spirit and true scope of the invention as claimed.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000